

TY2-48 SERIES TY2SYS-48 SERIES

HEATED DISPLAY SYSTEMS







• HALO HEAT ... a controlled, uniform heat source that gently holds and surrounds food for better appearance, taste, and longer holding life.

- Holds and displays hot food fresh and moist for hours without adding water.
- Expandable system to meet your specific requirements.
- Matches profile of leading refrigerated display case.

• HOT DISPLAY CASE

- Curved glass styling.
- Displays hot food without condensation on glass.
- Thermostatically controlled heat source radiates from the base of the display case in multiple heat zones.
- Overhead light zones with shatterproof coated bulbs.
- Holds a full range of standard (gastronorm) pan sizes, full-size or half-size sheet pans.
- Tempered sliding glass doors reflect heat back into the products and mirror the display to enhance merchandising effect.

• DECORATOR BASE

Standard black painted front and end panels.

• SELF-SERVICE HOT DISPLAY

- Customer self-service opening is available across the full length of case.
- Front mounted heat-guard provides customer protection.



TY2SYS-48

The display case is constructed of 18 gauge, non-magnetic stainless steel. A tempered glass front encloses the display case and can be lifted to a 90 degree angle for easy cleaning. Removable, sliding glass doors on the operator side are included. Sliding door tracks have a "clean sweep" cutout allowing for easy cleaning and crumb removal. Framed end glass with rubber gasket material protects glass edges from chipping and breakage. The base is divided into two (2) individually managed heat zones with each zone controlled by a separate thermostat with a range of 1 through 10 and heat-on indicator light. Overhead lights are controlled by ON/OFF switches in two (2) light zones. Two (2) 125V plug outlets are available as an option on 120/208-240V units only. Counter-top display cases include one set of 4" (102mm) legs.

	TY2-48	- 48"	(1219mm)	length
--	--------	-------	----------	--------

[☐] TY2SYS-48/P - 48" (1219mm) length, with base, 47-5/16" (1202mm) self-service opening across full length of case front





FACTORY INSTALLED OPTIONS

- The system base is not sold as a separate item. Order the full TY2SYS model to receive the base.
- Panel Color Choices
 - **⇒**Specify color choice:
 - ☐ Black, standard
 - ☐ Stainless Steel, optional
 - ☐ Custom Color, optional





W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A.

PHONE: 262.251.3800 800.558.8744 U.S.A./CANADA

FAX: 262.251.7067 800.329.8744 U.S.A. ONLY

DUE TO ONGOING PRODUCT DEVELOPMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.


[☐] **TY2SYS-48** - 48" (1219mm) length, with base


[☐] TY2-48/P - 48" (1219mm) length, 47-5/16" (1202mm) self-service opening across full length of case front



TY2-48 SERIES TY2SYS-48 SERIES

HEATED DISPLAY SYSTEMS





INSTALLATION REQUIREMENTS

Display case must be installed level. The display case must not be installed in any area where it may be affected by steam, grease, dripping water, high temperatures, or any other severely adverse conditions.

Do not install a heated display case near a cold air source such as a freezer, air conditioning vents, or in any area where outside air fluctuation can affect performance.

WEIGHT					
MODEL	NET	SHIP			
TY2-48	225 lb (116 kg)	585 lb (265 kg)			
TY2SYS-48	475 lb (215 kg)	602 lb (273 kg)			
TY2-48/P	265 lb (120 kg)	585 lb (265 kg)			
TY2SYS-48/P	475 lb (215 kg)	602 lb (273 kg)			
CRATED DIMENSIONS (EST.): H X W X D					

TY2-48: 45" x 60" x 55" (1143mm x 1524mm x 1397mm)
TY2SYS-48: 65" x 60" x 55" (1651mm x 1524mm x 1397mm)

DIMENSIONS (H X W X D)

EXTERIOR, COUNTER-TOP MODEL WITH LEGS:

33-11/16" x 48" x 49" (830mm x 1219mm x 1242mm)

EXTERIOR, WITH BASE:

52-3/16" x 48" x 51-5/16" (1325mm x 1219mm x 1304mm)

WELL DIMENSIONS (W X L X D):

27-3/16" x 45-5/16" x 4-1/2" (690mm x 1151mm x 114mm)

ELECTRICAL					
VOLTAGE	PHASE	CYCLE/HZ	AMPS	kW	
120/208-240 (UL)	1	50/60	13.8	3.3	NEMA L14-20P
at 208	1	50/60	11.6	2.5	20A, 250V PLUG
at 240	1	50/60	13.0	3.1	2011) 2001 1200
230 (CE)	1	50/60	12.6	2.9	
230	1	50/60	12.6	2.9	BARE END, NO PLUG

PAN CONFIGURATION	*	
PAN SIZE	DIMENSIONS	QTY.
FULL-SIZE & ONE-THIRD**:	12" x 20" x 2-1/2" (GN 1/1)	3
	12" x 6" x 2-1/2" (GN 1/3)	3
HALF-SIZE & ONE-THIRD**:	12" x 10" x 2-1/2" (GN 1/2)	6
	12" x 6" x 2-1/2" (GN 1/3)	3
FULL-SIZE SHEET PANS:	18" x 26" x 1"	2
MAX. CAPACITY/VOLUME:	48 lbs (22 kg)	
	30 qts (36 L)	
4.75	.1 11 1	

^{*} Pans are not included with display case.

SPECIFICATIONS

- Six (6) overhead lights with two (2) light zones.
- Two (2) base heat zones with two (2) adjustable thermostats with a range of 1 through 10, and two (2) heat-on indicator lights.
- Two (2) tinted, reflective, tempered glass sliding doors on operator side.
- One (1) 10" x 36" (254mm x 914mm) operator-side work shelf.
- Self-serve model TY2-48/P has a self-serve pan insert 26-7/16" x 45-3/16" x 2" (672mm x 1148mm x 51mm) and includes two (2) Wire Pan Grids.

OPTIONS & ACCESSORIES		_	
☐ BUTTING KIT	CONTACT FACTORY	PANEL KIT, SYSTEM END PANEL	
☐ CARVING STATION	5001874	☐ BLACK FORMICA EXTERIOR	5004570
☐ GAUGE, INTERIOR AMBIENT TEM	P. GU-33384	☐ STAINLESS STEEL EXTERIOR,	
\Box GLASS, TEMPERED END PANE, BRON	IZE KIT 5008530	POLISHED STAINLESS STEEL INTERIOR	5004571
☐ INDEPENDENT ELECTRICAL OUTL	LET 5001781	☐ PAN INSERT, SELF-SERVICE 4" (102mm) DEEP	1001990
PANEL KIT, COUNTER TOP		☐ PLATFORM SCALE	55265
☐ BRUSHED STAINLESS STEEL	5004566	☐ SHEET PAN DIVIDER BAR PACKAGE	5002802
☐ CUSTOM COLOR	5004625		
PANEL KIT, SYSTEM		☐ TEMPERATURE PROBE	5004916
☐ BRUSHED STAINLESS STEEL	5004567	☐ THERMOSTAT GUARD COVER PLATE	5007660
☐ CUSTOM COLOR	5004626	\square WORK SHELF WITH GRAVY LANE	5005638



W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A.

PHONE: 262.251.3800 800.558.8744 U.S.A./CANADA FAX: 262.251.7067 800.329.8744 U.S.A. ONLY

^{**} Will also accept 4" (100mm) deep pans.